

HIGH QUALITY

The ground protection mats can withstand high loads, are nonslip, resistant to liquids and chemicals and have a long durability.

MANY PURPOSES

Ground protection mats can be used on construction sites, as temporary walkways, driveways, surface protection etc.

LARGE SELECTION

Our protection mats are available in different standard sizes and thicknesses. See the overview below. For other sizes and colors: contact the responsible Key Account Manager in your area.

All mats come with the option of handles and holes, and you can have your own logo on the mat.

We also sell various connectors and transport boxes, allowing the mats to be connected to each other and easily transported.



DAN-Board Xtreme

DAN-Board Xtreme is a ground protection mat with an extra strong structure designed for challenging working environments. Xtreme has a rough surface structure that significantly improves grip and slip resistance. This feature ensures that your machines stay in place, even in adverse conditions, reducing the risk of the risk of accidents and injuries



LENGTH	2.000 - 2.400 - 3.000 mm
WIDTH	1.000 - 1.200 mm
THICKNESS	18 - 22 mm
COLORS	Black



Material	Recycled plastic. Type: LDPE
Delivery method / Application	Mats / Ground Protection Mats
Standard surface	Structure 4 mm
Machining	Sawing, drilling, milling, shaping, welding

Mechanical properties (at 23°C)	DIN EN ISO	Units	
Density	1183	g/cm3	0,94
Tensile stress	527	MPa	12
Tensile strength	527	MPa	7
Stretch extension	527	%	140
Pull E-Modul	527	MPa	450
Bend E-Modul	178	MPa	500
Impact resistance	179-1/1eU	KJ/m2	no breaks
Abrasion resistance (at 1000 g)	ASTM-D-4060-10	Wear Index	ca. 45

Thermal properties		Units	
min./max. usage temp.		°C	-40 to 70
Linear thermal expansion	DIN EN ISO 11359	mm/(m•10°C)	1,8

Chemical and physical properties		
Fire class	EN 13501-1:2018	Efl

Products are generally highly resistant to acids, alkalis and solvents